

4

3

▽


2

1

REVISIONS

NO.	DESCRIPTION	ECN NO.	DATE
	INITIAL RELEASE	ECN-2201405040	2014.05.28
△			

Please Approve this Drawing	
Date	
Signature	



NOTE;

- Material
Plunger: SK4 Au Plated
Barrel: Brass Au Plated
Spring: SUS304 Not Au Plated
- Electrical
Rated current : 3A Max.
Contact resistance: 100 mohm maximum at working stroke(quiescence)
- Mechanical
Full stroke: 6.30 mm
Spring Force :230g±20% at 4.20 mm working stroke
Durability: 100,000 cycles(minimum)
- Harmful material control please follow DOC. NO."DQ03050"

DRAWN	linyushou	SCALE:	1 : 1	UNIT	mm	DRAWING NO.	P-25T1-1535
CHECKED		SHEET:	1 of 1	PROJECT		TITLE. Test Probe	
APPROVED		DATE:	2014.05.28	VER.	A.0		
THE UNMARKED TOLERANCE ARE AS BELOW :						C.C.P. (DG) CONTACT PROBES CO.,LTD.	
LENGTH		ANGLE		东莞中探探针有限公司			
0~6.0	±0.05mm	0.	±2.0°	The information in this document is property of C.C.P company and should not be copied or reproduced in any other way, without written permission.			
>6~30	±0.10mm	0.0	±1.0°				
>30~120	±0.15mm	0.00	±0.50°				

4

3

▽

2

1